

WHE00007

EN



TECHNICAL DETAILS



MATERIAL

EXTERNAL SHELL:
ABS

INTERNAL SHELL:
HD Polystyrene

HEADBAND:
Soft PA Nylon



SIZE

Universal-adjustable
from 51 to 63 cm



WEIGHT

480 g



STANDARD

EN 14052

Protection against front, rear and side impacts in conformity with EN 12492
Clauses 4.2.1.2, 4.2.1.3, 4.2.1.4 shock energy absorption capacity
Protection from impacts and penetration in conformity with EN 397
Clause 5.1.1 Shock Absorption
Clause 5.1.2 Penetration Resistance
EN 397 ADDITIONAL TESTS: LD



WHE00007-201
WHITE



WHE00007-202
YELLOW



WHE00007-204
RED



TEMPERATURE OF USE

-10°C / +50°C



CATEGORY

II

TECHNOLOGIES



2DRY

A quick-drying technical fabric that accelerates the dispersion of sweat and moisture to the surface of the helmet padding for a drier, more comfortable wear.



MICROMETRICAL ADJUSTMENT

The micrometrical size regulation system positioned at the rear of the helmet provides quick and precise adjustment, even when wearing gloves.



EARMUFF ATTACHMENT SLOTS

Attachment points enable mounting earmuffs to helmet through bayonet adaptors.



INTEGRATED LAMP CLIPS

Designed with four built-in, nylon lamp attachment points.



VENTILATION CHANNELS

Ten air intakes that enhance breathability and comfort.



VISOR ATTACHMENT POINTS

Attachment points enable screw fastening of visor to helmet.

PERFORMANCES

Protection against top impacts	K	5 kg from 2 m 100 J	Chinstrap release	K	>15 kg <25 kg
Protection against side, front and rear impacts	K	5 kg from 1 m 50 J	Retention system effectiveness	K	
Protection against the penetration of objects	K	3 kg from 1 m 30 J	Protection against side deformation	K**	

K Required performance tests

K** Additional tests performed to meet optional requirements

ADDITIONAL INFORMATION

GUARANTEE

3 years starting from the date of purchase.

3 **10**
YEARS GUARANTEE YEARS SHELF LIFE

SHELF LIFE

10 years starting from the date of manufacture. The helmet must be checked regularly and before each use to detect the presence of any damage such as cracks, detachments, deformities, or peeling that represent factual elements of the state of deterioration of the helmet. Helmets that have suffered a severe impact shall be replaced even if they do not show obvious signs of damage.

CLEANING

Clean the helmet with the KASK Helmet cleaner or with water, neutral pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). The KASK Liner Refresher is available to neutralise unpleasant odours.

STORAGE

The helmet should be stored away from direct sunlight or source of heat. We recommend the use of the KASK drawstring helmet bag to protect the helmet when not in use.

ADHESIVE APPLICATION

Do not apply adhesives, stickers or use paint and solvents on the helmet that do not comply with the manufacturer's specifications. Any alteration or intervention may impair its protective function.

SAFETY ACCESSORIES



WVI00018
VISOR V2 PLUS



WVI00024
FACE SHIELD



WVI00003
VISOR FULL FACE



WVI00006
MESH VISOR



WHP00004/5/6
EARMUFFS



WLA00001/2/3
HEADLAMPS



WPA00007
WINTER CAP



WAC00020/24
NECK SHADE



WAC00032/33
NECK SHIELD RW



WAC00036/37
SUN SHIELD

DISCOVER MORE



SCAN FOR
COMPLETE
COLLECTION